

SURFACE WATERTIGHT BOXES WITH SMOOTH WALLS

TECHNICAL REFERENCES

- Approval certificate CSN n° 1100428
- Products conform to the essential requisites of the directive CSN EN 60670-1:05
- Double insulation 
- Products made of ABS alogen free.
- Protection degree (EN 60529): IP44 / IP55 / IP65
- Temperature during installation: - 5°C - + 60°C
- Glow wire test: 650°C IEC 60695-2-11
- Ageing test according to CEI 23-48: 7 days at 70°C
- Pressure test with the sphere according to CEI 23-48: 70°C
- Possibility to get complete insulation according to EN 60439
- Shock resistance: IK 07 IP44 and IK08 IP55, IP65
- Large range of accessories to customize on different applications.
- Centring signs on the walls.
- Gaskets in EPDM.
- **CSN EN 60670-1:05**
Casing for devices for electrical installation for domestic and similar uses.
Part 1: general prescriptions
- AVAILABLE ON REQUEST WITH HEAT RESISTANCE V0 960°C GLOW WIRE TEST



GR17000



GR17002



GR17006



GR17010



GR17012



GR17014

• SURFACE WATERTIGHT BOXES WITH SMOOTH WALLS

CODE	DESCRIPTION				MARKS
GR17000	SURFACE BOX SMOOTH WALLS IP44 Ø 83 X 45	3X180	0.0800	9.80	  
GR17001	SURFACE BOX SMOOTH WALLS IP44 Ø 68 X 40	3X294	0.0800	10.00	  
GR17002	SURFACE BOX SMOOTH WALLS IP65 55 X 130 X 60	3X130	0.0800	13.00	  
GR17003	SURFACE BOX SMOOTH WALLS IP44 83 X 83 X43	3X180	0.0800	9.80	  
GR17004	SURFACE BOX SMOOTH WALLS IP65 100 X 100 X 60	1X99	0.0800	14.00	  
GR17006	SURFACE BOX SMOOTH WALLS IP65 130 X 90 X 65	1X80	0.0800	12.00	  
GR17008	SURFACE BOX SMOOTH WALLS IP65 150 X 110 X 75	1X50	0.0800	11.00	  
GR17010	SURFACE BOX SMOOTH WALLS IP65 150 X 140 X 75	1X40	0.0800	10.00	  
GR17011	SURFACE BOX SMOOTH WALLS IP65 190 X 140 X 75	1X24	0.0800	10.00	  
GR17012	SURFACE BOX SMOOTH WALLS IP65 170 X 170 X 75	1X24	0.0800	8.00	  
GR17013	SURFACE BOX SMOOTH WALLS IP65 170 X 170 X 128	1X30	0.1600	13.00	  
GR17014	SURFACE BOX SMOOTH WALLS IP65 240 X 190 X 90	1X14	0.0800	8.00	  